

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO). I	ILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/040,268		10/30/2001	Randy Marchetti	1570-005	9580	
33461	7590	03/01/2004		EXAMINER		
	AN LAW	GROUP RAL AVENUE	CHOI, JACOB Y			
SUITE 114		AND AVEIVOE		ART UNIT	PAPER NUMBER	
PHOENIX, AZ 85004				2875		

DATE MAILED: 03/01/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

					A*			
		Applicatio	n No.	Applicant(s)				
	10/040,26	8	MARCHETTI, RANDY					
Office .	Action Summary	Examiner		Art Unit				
		Jacob Y Cl		2875				
The MAILII Period for Reply	NG DATE of this communication a	ppears on the	cover sheet with the c	orrespondence add	Iress			
THE MAILING DA - Extensions of time ma after SIX (6) MONTHS - If the period for reply s - If NO period for reply - Failure to reply within the service of the service o	STATUTORY PERIOD FOR REP ATE OF THIS COMMUNICATION by be available under the provisions of 37 CFR of the mailing date of this communication, becified above is less than thirty (30) days, a resist specified above, the maximum statutory perion he set or extended period for reply will, by state the Office later than three months after the mainustment. See 37 CFR 1.704(b).	I. 1.136(a). In no ever ply within the statur d will apply and will ute, cause the appli	nt, however, may a reply be tim tory minimum of thirty (30) days expire SIX (6) MONTHS from cation to become ABANDONEI	nely filed s will be considered timely, the mailing date of this cor O (35 U.S.C. § 133).	mmunication.			
Status								
1) Responsive	to communication(s) filed on 19	November 20	<u>03</u> .					
2a) This action	is FINAL . 2b)⊠ Th	nis action is no	on-final.	•				
· ·	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.							
Disposition of Claim	IS							
4a) Of the a 5) ☐ Claim(s) 6) ☑ Claim(s) <u>1-3</u> 7) ☐ Claim(s)	22 is/are pending in the application bove claim(s) is/are withdown is/are allowed. 22 is/are rejected. is/are objected to. are subject to restriction and	rawn from cor						
Application Papers								
10)□ The drawing Applicant ma Replacemen	ation is objected to by the Examin(s) filed on is/are: a) and any not request that any objection to the drawing sheet(s) including the corrected to by the	ccepted or b)[ne drawing(s) b ection is require	e held in abeyance. See ed if the drawing(s) is obj	e 37 CFR 1.85(a). lected to. See 37 CF				
Priority under 35 U.S	S.C. § 119							
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 								
	on's Patent Drawing Review (PTO-948) ire Statement(s) (PTO-1449 or PTO/SB/0	98)	4) Interview Summary Paper No(s)/Mail Do 5) Notice of Informal F 6) Other:	ate	⊦152)			

Art Unit: 2875

DETAILED ACTION

Claim Rejections - 35 USC § 103

- 1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 2. Claims 1-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Bertling et al. (USPN 5,353,203) in view of Sumada et al. (USPN 6,439,753).

Regarding claims 1, 9, & 18 Bertling et al. discloses a reflector (12, 20) comprising a first (20) and second (12) reflective concave surface regions adjacent to one another (column 3, lines 10-30), the first reflective (20) concave surface region comprising a first curvature for directing light emanating from a first focal point adjacent to but spaced apart from the first reflective concave surface region into a near field beam (low beam headlight; column 4, lines 40-65), and the second (12) reflective concave surface region comprising a second curvature for directing light emanating from a second focal point adjacent to but spaced apart from the second reflective concave surface region into a far field beam (column 4 & 5, lines 65-35), a first light source positioned substantially at the first focal point (at the light source 22), the first light source comprising an incandescent lamp or gas discharged lamp (column 3, lines

Art Unit: 2875

10-20), a second light source positioned substantially at the second focal point (at the light source 14), the second light source comprising an incandescent lamp or gas discharged lamp (column 2, lines 55-65), and a light-transmissive cover fitted over the reflector (16).

Bertling et al. discloses a reflector comprising first and second reflective concave surface regions adjacent to one another, the first reflective concave surface region comprising a first curvature for directing light emanating from a first focal point adjacent to but spaced apart from the first reflective concave surface region into a near filed beam (low beam headlight; column 4, lines 40-65), the first reflective concave surface region having a first peripheral edge (outer ring of the reflector 20) with opposite ends and a first internal edge (discontinuity) extending between the opposite ends of the first peripheral edge, the second reflective concave surface region comprising a second curvature for directing light emanating from a second focal point adjacent to but spaced apart from the second reflective concave surface region into a far field beam (column 4 & 5, lines 65-35), the second reflective concave surface region having a second peripheral edge (outer ring of the reflector 12) with opposite ends and a second internal edge (discontinuity) extending between the opposite ends of the second peripheral edge, the respective opposite ends of the first and second peripheral edges interfacing one another (connection point/line of outer shape of the reflector 12 & 20 and discontinuity) and the first and second internal edges interfacing one another (discontinuity between the upper reflector portion 12 and the lower reflector portion 20), a first light source positioned substantially at the first focal point, the first light source

comprising an incandescent lamp or gas discharged lamp, a second light source positioned substantially at the second focal point, the second light source comprising an incandescent lamp or gas discharged lamp, and a light-transmissive cover fitted over the reflector.

Bertling et al. discloses a first reflective concave surface region comprising a first curvature for directing light emanating from a first focal point adjacent to but spaced apart from the first reflective concave surface region into a near field beam, the first reflective concave surface region having a first arcuate peripheral edge with opposite ends and a first internal edge extending between the opposite ends of the first arcuate peripheral edge, a second reflective concave surface region adjacent the first reflective concave surface region and comprising a second curvature for directing light emanating from a second focal point adjacent to but spaced apart from the second reflective concave surface region into a far field beam, the second reflective concave surface region having a second arcuate peripheral edge with opposite ends and a second internal edge extending between the opposite ends of the second arcuate peripheral edge, the respective opposite ends of the first and second peripheral edges interfacing one another to define a substantially circular outer perimeter of the reflector and the first and second internal edges interfacing one another.

Bertling et al. discloses the claimed invention except a specific light source(s) that is either a halogen or a high intensity discharge bulb. Sumada et al. teaches that it is known to utilize a well-used light source, such as a halogen & HID, for a vehicle headlight. It would have been obvious to one having ordinary skill in the art at the time

the invention was made to use modification in Bertling et al. as taught by Sumada et al. in order to utilize well known and different light source that is suitable for a vehicle head lighting system.

Regarding claim 2, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the reflector is substantially rounded.

Regarding claim 3, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the reflector is substantially circular.

Regarding claim 4, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the first and the second reflective concave surface regions are integral with one another.

Regarding claim 5, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the reflector is a unitary piece.

Regarding claim 6, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the first concave reflective surface region is parabolic and has a first optical axis passing through the first focal point, and further wherein the second concave reflective surface region is parabolic and has a second optical axis passing through the second focal point.

Regarding claim 7, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the second curvature is different than the first curvature (figure 2).

Regarding claim 8, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the high intensity discharge light source comprises a xenon light source (gas discharge lamps includes xenon light source).

Regarding claim 10, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the first and second peripheral edges are arcuate (figure 2).

Regarding claim 11, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the first and second peripheral edges define a substantially circular outer perimeter of the reflector (figure 2).

Regarding claim 12, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the first and second reflective concave surface regions are integral with one another (figure 1 & 2).

Regarding claim 13, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the reflector is a unitary piece.

Regarding claim 14, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the first and second internal edges interface and adjoin one another to define a ridge (21).

Regarding claim 15, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the first concave reflective surface region is parabolic and has a first optical axis passing through the first focal point, and further wherein the second concave reflective surface region is parabolic and has a second optical axis passing through the second focal point.

Regarding claim 16, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the second curvature differs from the first curvature.

Regarding claim 17, Bertling et al. in view of Sumada et al. discloses the claimed invention, explained above. In addition, Bertling et al. discloses the high intensity discharge light source comprises a xenon light source.

Regarding claim 19, Bertling et al. discloses the first and second reflective concave surface regions are integral with one another.

Regarding claim 20, Bertling et al. discloses the reflector is a unitary piece.

Regarding claim 21, Bertling et al. discloses the first concave reflective surface region is parabolic and has a first optical axis passing through the first focal point, and further wherein the second concave reflective surface region is parabolic and has a second optical axis passing through the second focal point.

Regarding claim 22, Bertling et al. discloses the second curvature is different from the first curvature.

3. Claims 1-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Sato (USPN 6,120,169) in view of Sumada et al. (USPN 6,439,753).

Application/Control Number: 10/040,268

Art Unit: 2875

Regarding claims 1, 9, & 18, Sato discloses a reflector comprising a first and second reflective concave surface regions adjacent to one another, the first reflective concave surface region comprising a first curvature for directing light emanating from a first focal point adjacent to but spaced apart from the first reflective concave surface region into a near field beam, and the second reflective concave surface region comprising a second curvature for directing light emanating from a second focal point adjacent to but spaced apart from the second reflective concave surface region into a far field beam, a first light source positioned substantially at the first focal point, the first light source comprising a high intensity discharge light source, a second light source positioned substantially at the second light source comprising a halogen light source, and a light-transmissive cover fitted over the reflector.

Page 8

Sato discloses a reflector comprising first and second reflective concave surface regions adjacent to one another, the first reflective concave surface region comprising a first curvature for directing light emanating from a first focal point adjacent to but spaced apart from the first reflective concave surface region into a near filed beam the first reflective concave surface region having a first peripheral edge with opposite ends and a first internal edge extending between the opposite ends of the first peripheral edge, the second reflective concave surface region comprising a second curvature for directing light emanating from a second focal point adjacent to but spaced apart from the second reflective concave surface region into a far field beam, the second reflective concave surface region having a second peripheral edge with opposite ends and a second internal edge extending between the opposite ends of the second peripheral

edge, the respective opposite ends of the first and second peripheral edges interfacing one another and the first and second internal edges interfacing one another, a first light source positioned substantially at the first focal point, the first light source comprising a halogen bulb or an electric discharge bulb, a second light source positioned substantially at the second focal point, the second light source comprising a halogen bulb or an electric discharge bulb, and a light-transmissive cover fitted over the reflector.

Sato discloses a first reflective concave surface region comprising a first curvature for directing light emanating from a first focal point adjacent to but spaced apart from the first reflective concave surface region into a near field beam, the first reflective concave surface region having a first arcuate peripheral edge with opposite ends and a first internal edge extending between the opposite ends of the first arcuate peripheral edge, a second reflective concave surface region adjacent the first reflective concave surface region and comprising a second curvature for directing light emanating from a second focal point adjacent to but spaced apart from the second reflective concave surface region into a far field beam, the second reflective concave surface region having a second arcuate peripheral edge with opposite ends and a second internal edge extending between the opposite ends of the second arcuate peripheral edge, the respective opposite ends of the first and second peripheral edges interfacing one another to define a substantially circular outer perimeter of the reflector and the first and second internal edges interfacing one another.

Sato discloses the claimed invention except a specific light source(s) that is either a halogen or a high intensity discharge bulb. Sumada et al. teaches that it is

known to utilize a well-used light source, such as a halogen & HID, for a vehicle headlight. It would have been obvious to one having ordinary skill in the art at the time the invention was made to use modification in Sato as taught by Sumada et al. in order to utilize well known and different light source that is suitable for a vehicle head lighting system.

Regarding claim 2, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the reflector is *substantially* rounded.

Regarding claim 3, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the reflector is *substantially* circular.

Regarding claim 4, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the first and the second reflective concave surface regions are integral with one another.

Regarding claim 5, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the reflector is a unitary piece.

Regarding claim 6, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the first concave reflective surface region is parabolic and has a first optical axis passing through the first focal point, and further wherein the second concave reflective surface region is parabolic and has a second optical axis passing through the second focal point.

Regarding claim 7, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the second curvature is different than the first curvature.

Regarding claim 8, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the high intensity discharge light source comprises a xenon light source.

Regarding claim 10, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the first and second peripheral edges are arcuate.

Regarding claim 11, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the first and second peripheral edges define a substantially circular outer perimeter of the reflector.

Regarding claim 12, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the first and second reflective concave surface regions are integral with one another.

Regarding claim 13, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the reflector is a unitary piece.

Regarding claim 14, Sato discloses the first and second internal edges interface and adjoin one another to define a ridge.

Regarding claim 15, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the first concave reflective surface region is parabolic and has a first optical axis passing through the first focal point, and further wherein the second concave reflective surface region is parabolic and has a second optical axis passing through the second focal point.

Art Unit: 2875

Regarding claim 16, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the second curvature differs from the first curvature.

Regarding claim 17, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the high intensity discharge light source comprises a xenon light source.

Regarding claim 19, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the first and second reflective concave surface regions are integral with one another.

Regarding claim 20, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the reflector is a unitary piece.

Regarding claim 21, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the first concave reflective surface region is parabolic and has a first optical axis passing through the first focal point, and further wherein the second concave reflective surface region is parabolic and has a second optical axis passing through the second focal point.

Regarding claim 22, Sato in view of Sumada et al. discloses the claimed invention, explained above. In addition, Sato discloses the second curvature is different from the first curvature.

Response to Arguments

Art Unit: 2875

4. Applicant's arguments with respect to claims 1-22 have been considered but are most in view of the new ground(s) of rejection.

Conclusion

5. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Ashizawa et al. (USPN 6,394,636) – vehicular headlamp Fujinami et al. (USPN 6,543,920) – vehicle headlamp Mochizuki et al. (USPN 6,652,130) – vehicle headlamp

6. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Jacob Y Choi whose telephone number is (571) 272-2367. The examiner can normally be reached on Monday-Friday (10:00-7:00).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Sandra O'Shea can be reached on (571) 272-2378. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

JC

Sandra O'Shea
Supervisory Patent Examiner
Technology Center 2800